

Oklahoma Department of Corrections

Demographics

(as of June 29, 2012)

<u>RACE</u>	<u>NO.</u>	<u>PERCENT</u>
Caucasian	13,886	53.6%
African American	7,485	28.9%
Native American	2,410	9.3%
Hispanic	1,972	7.6%
Other	136	0.5%

<u>OFFENSE</u>	<u>NO.</u>	<u>PERCENT</u>
Distribution Drugs	4,702	18.2%
Assault	2,829	10.9%
Poss/Obtain Drugs	2,514	9.7%
Robbery	2,251	8.7%

Dick Conner Correctional Center

Statistics

Opened: August 1979
Location: Hominy
Security: Medium
Capacity: 1,196
Gender: Male

STANDING PROUD

MISSION

To Protect the Public
To Protect the Employee
To Protect the Offender

VISION

The Department of Corrections will
create a culture that

Empowers Individuals
Encourages Teamwork
Employs Best Practices
Embraces Diversity

Dick Conner Correctional Center
P.O. Box 220
Hominy, OK 74035-0220
(918) 594-1300

Division III - Institutions
201 E. Cherokee Avenue
McAlester, OK 74501-5329
(918) 423-4144

Oklahoma Department of Corrections
3400 Martin Luther King Avenue
Oklahoma City, OK 73111-4298
(405) 425-2500

Produced by the
Executive Communications Office 3/2013

OKLAHOMA
DEPARTMENT OF CORRECTIONS

Dick Conner

CORRECTIONAL CENTER

Terry Martin
Warden

History

The post OSP riot master plan included a medium security facility to be constructed in the Tulsa area. It was eventually decided that the facility would be built just north of Hominy, Oklahoma, within the boundaries of the original Osage Indian Reservation. Originally, the facility was to be named the “Hominy Medium Security Facility.” It was next decided that the facility would be named Jess Dunn Correctional Center in honor of the former OSP warden killed in an escape attempt. However, a 1977 Joint Senate-House Resolution renamed the facility, for the third and final time, the Dick Conner Correctional Center. The facility’s namesake is R. B. “Dick” Conner, a former local Sheriff of Osage County and former OSP warden. The facility was built for \$12.8 million. Dick Conner Correctional Center received its first offenders in August, 1979, and reached its original design capacity of 400 during the spring of 1980.